

Marmi Tile Collection



Staturio

Sizes Available (All Rectified)

- ❖ 30x30
- ❖ 30x60
- ❖ 60x30
- ❖ 40x80
- ❖ 80x80

Please note the range offers feature Mosaics & Chevron Patterns

Finishes Available

- ❖ Matt finish
- ❖ Polished

Marmi Tile Collection



Calacatta Oro

Sizes Available (All Rectified)

- ❖ 30x30
- ❖ 30x60
- ❖ 60x30
- ❖ 40x80
- ❖ 80x80

Please note the range offers feature Mosaics
& Chevron Patterns

Finishes Available

- ❖ Matt finish
- ❖ Polished

Marmi Tile Collection



Carrarra

Sizes Available (All Rectified)

- ❖ 30x30
- ❖ 30x60
- ❖ 60x30
- ❖ 40x80
- ❖ 80x80

Please note the range offers feature Mosaics
& Chevron Patterns

Finishes Available


- ❖ Matt finish
- ❖ Polished

Marmi Tile Collection


Sheet mounted Mosaics 30x30



Sheet mounted
5x5




Herringbone



Hexagon



Sheet mounted
2.5x2.5 Tapeto



Woven Rectangles



Muretto



Basket weave

Installation and Care and a special note on polished glazed porcelain





The Marmi Tile collection evolved from a long and complex research project centered on creating high quality, glazed, polished porcelain marble with ultra high definition inkjet technology. The technical properties of the tile are outstanding, and to ensure the beauty of this product over time, it is essential to pay careful attention to certain details during installation.


Polished, glazed porcelain marble is stunning, however, like real marble itself, it is more subject to wear than matt tile. We do not recommend using this polished product in medium-high commercial traffic situations. Furthermore, for all installations, we advise placing mats or carpets in entranceways in order to remove moisture, dirt and sand from shoes as well as kitchen work areas and in bathrooms in shower, tub, and sink areas in order to absorb water and spills.

CARATTERISTICHE TECNICHE
Gres porcellanato smaltato impasto colorato

TECHNICAL FEATURES
Glazed through body porcelain stoneware

TECHNISCHE EIGENSCHAFTEN
Glasiertes Durchgefärbtes Feinsteinzeug

	NORME TEST N°	DESCRIZIONE DESCRIPTION	VALORE A NORMA REQUIRED STANDARD	VALORE I MARMI - MATT I MARMI RESULTS - MATT	VALORE I MARMI - LEV. I MARMI RESULTS - LEV.
	ISO 10545/4 	ASSORBIMENTO D'ACQUA WATER ABSORPTION ABSORPTION D'EAU WASSERAUFNAHME	≤ 0,5%	CONFORME	CONFORME
	ISO 10545/5 	RESISTENZA ALLA FLESSIONE BENDING STRENGTH RESISTANCE A LA FLEXION BIEGFESTIGKEIT	R ≥ 35 N/mm ²	CONFORME	CONFORME
	ISO 10545/8	COEFFICIENTE DI DILATAZIONE TERMICA LINEARE THERMAL EXPANSION COEFF. BETWEEN 20°C - 100°C COEFF. DE DILATATION THERMIQUE LINEAIRE ENTRE 20°C ET 100°C WÄRMEAUSSDEHNUNG ZWISCHEN 20°C UND 100°C	≤ 9x10 ⁻⁶ cm 30x60 - 12"x24"	9x10 ⁻⁶ C ⁻¹	OLUZIONI DI POSA  cm 40x80 - 16"x32"
	ISO 10545/9	RESISTENZA AGLI SBALZI TERMICI RESISTANCE TO THERMAL SHOCK RESISTANCE AUX CHOCs THERMIQUES TEMPERATURWECHSELBESTÄNDIGKEIT		RESISTE RESISTANT RESISTE BESTÄNDIG	RESISTE RESISTANT RESISTE BESTÄNDIG
	ISO 10545/11	RESISTENZA AL CAVILLO CRAZING RESISTANCE RESISTANCE AU TRASSAILAGE HAARRISSFESTIGKEIT		RESISTE RESISTANT RESISTE BESTÄNDIG	RESISTE RESISTANT RESISTE BESTÄNDIG
	ISO 10545/14	RESISTENZA ALLE MACCHIE STAIN RESISTANCE RESISTANCE AUX TACHES FLECKENFESTIGKEIT	min. Classe 3	CONFORME	CONFORME
	ISO 10545/13	RESISTENZA ALL'ATTACCO CHIMICO CHEMICAL RESISTANCE RESISTANCE À L'ATTACQUE CHIMIQUE FÄHIG GEGEN SÄUREN UND LAUGEN	min. GB	CONFORME	CONFORME
	ISO 10545/2	LUNGHEZZA E LARGHEZZA LENGTH AND WIDTH LONGUEUR ET LARGEUR LÄNGE UND BREITE	± 0,5%	CONFORME	CONFORME
	ISO 10545/2	SPESSORE THICKNESS ÉPAISSEUR STÄRKE	± 5%	CONFORME	CONFORME
	ISO 10545/2 	ORTOGONALITÀ WEDGING ORTHOGONALITÉ RECHTWINKLICHKEIT	± 0,6%	CONFORME	CONFORME
	ISO 10545/2	PLANARITÀ WARPAGE PLANÉITÉ EBENFLÄCHIGKEIT	± 0,5%	CONFORME	CONFORME
	ISO 10545/12	RESISTENZA AL GELO FROST RESISTANCE RESISTANCE AU GEL FROSTBESTÄNDIGKEIT		RESISTE RESISTANT RESISTE BESTÄNDIG	RESISTE RESISTANT RESISTE BESTÄNDIG
	ISO 10545/6	RESISTENZA ALL'ABRASIONE PROFONDA DEEP ABRASION RESISTANCE RESISTENCE À LABRASION PROFONDE TIEFENVERSCHEISSBESTÄNDIGKEIT	< 175 mm ³	128 mm ³	
	BOT 3000 WET DCOF	RESISTENZA ALLO SCIVOLAMENTO SLIP RESISTANCE RESISTANCE AU GLISSEMENT BESTIMMUNG DER RUTSCHEMMEDE EIGENSCHAFT	IV 0,42	Tile 1 : 0.57 Tile 2 : 0.61 Tile 3 : 0.58	
	DIN 51130 R	WATER, OIL, GREASE, ETC. CREATE SLIPPERY CONDITIONS. FLOOR APPLICATIONS WITH EXPOSURE TO THESE CONDITIONS REQUIRE EXTRA CAUTION IN PRODUCT SELECTION.		R9	



S

p

e

r

u

n

a

c

r

r

e

t

t

a

r

e

a

l

i

z

a

z

i

o

n

e

s

i

c

o

n

s

i

g

l

i

a

d

i

p

o

s

a

r

e

i

f

o

r

m


a

t

i

l

i

lunghezza 60 cm e 80 cm, sfalsati
massimo 20 cm o 

a correre di

Precious Marble 

p

o

s

a